

20% Fluorine Nitrogen mixture. 20% F₂/N₂ mixture

Product information

Fluorine mixtures can be used mainly to clean non-plasma deposition chambers and diffusion furnace for silicon-based films. Typical mixtures is composed 20% F₂ in N₂ balance, and filled at high pressure in cylinder or larger packages. As fluorine is corrosive, toxic, and highly reactive, its storage entails risk; thus the use of 20% F₂/N₂ mixtures is treated as a safer manner to handle than pure F₂ at comparable total pressures.

Characteristics

Pale yellow gas with sharp odor. Ignites most organic materials and metals. Highly corrosive. See comprehensive handling directives. Gas density is heavier than air.

Physical data F₂

Molecular weight	[g/mol]	37.997		
Boiling point	at 1.013 bar [°C]	-188.2	at 14.5 psi [°F]	-306.74
Density	at 1.013 bar, 15 °C [kg/m ³]	1.608	at 1 atm., 70 °F [lb/ft ³]	0.098
Vapor pressure	at 0 °C [bar]	-	at 32 °F [psi]	-
	at 20 °C [bar]	-	at 70 °F [psi]	-
Flammability range in air (% volume)		Non combustible		

Physical data N₂

Molecular weight	[g/mol]	28.014		
Boiling point	at 1.013 bar [°C]	-195.8	at 14.5 psi [°F]	-320.42
Density	at 1.013 bar, 15 °C [kg/m ³]	1.185	at 1 atm., 70 °F [lb/ft ³]	0.072
Vapor pressure	at 0 °C [bar]	-	at 32 °F [psi]	-
	at 20 °C [bar]	-	at 70 °F [psi]	-
Flammability range in air (% volume)		Non combustible		

Product specification

	Specification	Min	Max	Purity	Typical impurities [ppm]		
					O ₂	CF ₄	HF
F ₂	20 %	19.5%	20.5%	≥99.9 %			
N ₂	Balance			≥99.999 %			
F ₂ /N ₂ mixture					50	20	100

→ [20% Fluorine Nitrogen mixture. Product datasheet.](#)

Packaging information

Package options	Cylinder internal volume	Cylinder material	Cylinder diameter	Cylinder height to valve outlet	Cylinder tare weight	Fill contents	Pressure (psig) @ 35°C	Valve outlet	Valve material
Cylinder	47L	Steel	235mm	1410mm	59KG	5MPa	725	CGA728	SS

Additional information

The information, recommendations, and data contained in this publication are intended to give basic guidance for safe handling and use of gases. It is essential for the safe use of gases that personnel are properly trained and are fully aware of the possible hazards. Further information and advice on any matter relating to the safe handling or use of these products may be obtained from Linde LienHwa.

For different requests and more information, email us at csc@linde-lienhwa.com.tw.